

FEATURES

- 40°C real wattage
- Meet with DOE & COC level VI
- Compliance with IEC/EN 62368-1
- Input voltage range for worldwide
- High compatibility in supporting notebooks
- Quality assurance by world's major notebook brands/makers
- Interchangeable laptop tips to support main-stream notebooks & ultrabooks charging
- Safety certified: CB, EMC, NRCAN, CCC, CSA_C/US, GOST, KCC, PSE, C-TICK, CE, UL, Nemko

AD9014

Dimension : L107*W47*H29.3mm
Total Max Power : 65W



INPUT SPEC.

Input Voltage	Input Frequency	Input Current
90~264Vac	47~63Hz	1.7A@90Vac
Efficiency		
87% @115/230Vac typical load		

OUTPUT SPEC.

Output Voltage	Load Range		Max Load (V)	Rated Power W
	Min.	Max.		
19V	0A	3.42A	18.05V~19.95V	65W

- Ripple Noise: Ripple with spike noise $\leq 350\text{mVp-p}$
- Hold-up Time: 5ms min.@115Vac input, full load
- Turn-on Delay: 5 sec. max.@115Vac

ENVIRONMENTAL SPEC.

- Operating Temperature: 0 ~ 40°C
- Storage Temperature: -31 ~ 60°C

APPLICATION

- NB
- Mini ITX
- Printer
- PC system
- Display device

GENERAL SPEC.

- Power protection: OVP, UVP, SCP, OTP, OCP
- AC Inlet: C6 (3Pin)
- Weight: 220g

*NOTE:

- 1) Tips information please refer to Compatibility List.
- 2) Not compatible with ALL model laptops for these brands.
- 3) Please check your notebook Tip dimension and Voltage before ordering.

OUTLINE DRAWING

