

FEATURES

- 40°C real wattage
- Meet with DOE & COC level VI
- Compliance with IEC/EN 62368-1
- Input voltage range for worldwide
- Safety certified: CB, EMC, FCC, NRCAN, UL
- Quality assurance by world's major notebook brands/makers
- Interchangeable laptop tips to support mainstream notebooks & ultrabooks charging

ADH013

Dimension : L88*W43*H26mm
Total Max Power : 65W



INPUT SPEC.

Input Voltage	Input Frequency	Input Current
90~264Vac	50+/-3Hz 60+/-3Hz	1.7A@90Vac

Efficiency

88+% @115 & 230Vac input

ENVIRONMENTAL SPEC.

- Operating Temperature: 0 ~ 40°C
- Storage Temperature: -31 ~ 60°C

APPLICATION

- NB
- Mini ITX
- Printer
- PC system
- Display device

OUTPUT SPEC.

Output Voltage	Load Range		Max Load (V)	Rated Power (Wattage)
	Min.	Max.		
19.5V	0A	3.33A	18.53V~20.47V	65W

- Ripple Noise: Ripple with spike noise \leq 380mVp-p
- Hold-up Time: 8ms sec.@3330mA load,110Vac/60Hz
- Turn-on Delay: less than 3 sec. @ MAX. load and 110Vac/60Hz input voltage

GENERAL SPEC.

- Power protection: OVP, UVP, SCP, OTP, OCP
- AC Inlet: C8 (2Pin)
- Weight: 175g

*NOTE :

- 1) Tips information please refer to Compatibility List.
- 2) Not compatible with ALL model laptops for these brands.
- 3) Please check your notebook Tip dimension and Voltage before ordering.

OUTLINE DRAWING

